CLAIMS

What is claimed is:

> 1

1. A method for clipping graphics primitives for display, comprising the steps of:

defining all vertices of a primitive using relational coordinates; using a clipping algorithm with a circular buffer to store input and output polygons of said primitive; and

for each vertex of said polygons:

indicating whether it is visible with respect to each plane of a view volume.

1

5

- 2. The method of Claim 1, wherein only vertices which are visible in all said planes are rasterized.
- 3. The method of Claim 1, wherein said using step is performed prior to any lighting fog, or texture calculations.
- 4. The method of Claim 1, wherein said primitive is a polygon.
- 5. The method of Claim, wherein said primitive is a triangle.
- 6. The method of Claim 1, wherein said relational coordinates are barycentric.
- 7. The method of Claim wherein said view volume is a frustrum.

App'n of 3Dlabs Inc., Ltd.: TD-143 Page 6

- 8. The method of Claim 1, wherein there are six or more planes in said view volume.
- 9. The method of Claim 1, wherein there are six planes in said view volume.
- 10. The method of Claim 1, wherein there are twelve planes in said view volume.
- 11. The method of Claim 1, wherein said clipping algorithm is the Sutherland and Hodgman polygon clipping algorithm.
- 12. The method of Claim 1, wherein vertex visibility in each of said planes is indicated by a bit flag.
- 13. The method of Claim 1, wherein vertex visibility is indicated by twelve bit code.
- 14. The method of Claim 1, wherein two circular buffers are used to store said input and output polygons.
- 15. The method of Claim 1, wherein said circular buffer has a maximum storage of sixteen vertices.



5

16. A geometry unit, comprising:

- circuitry to define all vertices of a primitive using relational coordinates;
- circuitry to implement a clipping algorithm with a circular buffer to store input and output polygons of said primitive; and
- whether it is visible with respect to each of plane of said view volume.
- 17. The geometry unit of Claim 16, wherein only vertices which are visible in all said planes are rasterized.
- 18. The geometry unit of Claim 16, wherein said clipping algorithm is implemented prior to any lighting, fog, or texture calculations.
- 19. The geometry unit of Claim 16, wherein said primitive is a polygon.
- 20. The geometry unit of Claim 16, wherein said primitive is a triangle.
- 21. The geometry unit of Claim 16, wherein said relational coordinates are barycentric.
- 22. The geometry unit of Claim 16, wherein said view volume is a frustrum.
- 23. The geometry unit of Claim 16, wherein there are six or more planes in said view volume.

App'n of 3Dlabs Inc., Ltd.: TD-143 Page 71

- 24. The geometry unit of Claim 16, wherein said clipping algorithm is the Sutherland and Hodgman polygon clipping algorithm.
- 25. The geometry unit of Claim 16, wherein vertex visibility in each of said planes is indicated by a bit flag.
- 26. The geometry unit of Claim 16, wherein two circular buffers are used to store said input and output polygons.
- 27. The geometry unit of Claim 16, wherein said circular buffer has a maximum storage of sixteen vertices.
- 28. A pipelined graphics system, comprising:
 - a transformation unit connected to:

transform a primitive into a clipping space, and

assign a fixed barycentric coordinate to each vertex of said primitive; and

a geometry unit connected to:

perform clip testing on said primitives,

clip said primitives, if necessary, according to said fixed barycentric coordinates, and

set an outcode value for each said vertex indicating whether it is visible with respect to each plane of a view volume.

29. The pipelined graphics system of Claim 28, wherein only vertices which are visible in all said planes are rasterized.

30. The pipelined graphics system of Claim 28, wherein said clipping is implemented prior to any lighting, fog, or texture calculations.

App'n of 3Dlabs Inc., Ltd.: TD-143 Page 72

10

5

- 31. The pipelined graphics system of Claim 28, wherein said primitive is a triangle.
- 32. The pipelined graphics system of Claim 28, wherein said view volume is a\frustrum.
- 33. The pipelined graphics system of Claim 28, wherein there are six or more planes in said view volume.
- 34. The pipelined graphics system of Claim 28, wherein said clipping uses the Sutherland and Hodgman polygon clipping algorithm.
- 35. The pipelined graphics system of Claim 28, wherein vertex visibility in each of said planes is indicated by a bit flag.
- 36. The pipelined graphics system of Claim 28, wherein two circular buffers are used to store said input and output polygons.
- 37. The pipelined graphics system of Claim 28, wherein said circular buffer has a maximum storage of sixteen vertices.

		a geometry and lighting accelerator connected to receive said
	5	graphics data comprising
		a transformation unit connected to:
		transform a primitive into a clipping space, and
£		assign a fixed barycentric coordinate to each vertex of said
	• •	primitive; and
	10	a geometry unit connected to
		perform clip testing on said primitives,
;		clip said primitives, if necessary, according to said fixed
Ġ		barycentric coordinates,
		set an outcode value for each said vertex indicating whether it
Щ	15	is visible with respect to each plane of a view volume, and
		output clipped graphics data to be rendered; and
Į L		video rendering hardware connected to receive said clipped graphics
5		data, generate graphics, and connected to display said graphics
s S		on said display hardware.
<u> </u>		
W	1	739. The computer system of Claim 38, wherein said clipping is imple-
Sa	PAY /	mented prior to any lighting, fog, or texture calculations.
	, 1	
		40. The computer system of Claim 38, wherein said primitive is a
		triangle.

41. The computer system of Claim 38, wherein said clipping uses the

App'n of 3Dlabs Inc., Ltd.: TD-143 Page 74

Sutherland and Hodgman polygon clipping algorithm.

38. A computer system comprising:

a processor connected to provide graphics data

display hardware;

- 42. The computer system of Claim 38, wherein vertex visibility in each of said planes is indicated by a bit flag.
- 43. The computer system of Claim 38, wherein two circular buffers are used to store said input and output polygons.
- 44. The method of Claim 38, wherein said video rendering hardware is a GLINT 500 TX.
- 45. The method of Claim 38, wherein said video rendering hardware is a GLINT PERMEDIA.
- 46. The method of Claim 38, wherein said processor is an X86-compatible processor.